ME-RT SERIES

REMOTE CONTROL MULTI-FUNCTION CRAWLER MACHINE

ONE PLATFORM.

FOUR STANDARD FUNCTIONS

ROTARY TILLAGE / WEEDING / DITCHING / BACKFILLING

- **WORKING WIDTH**
  800 mm
- **ENGINE**
  KOOP 195 diesel I 15 hp
- **REMOTE CONTROL**
  Up to 800 m
- **DIRECT OPERATION**
  Remote start / manual start



KOOP 195
Single-cylinder diesel engine I 15 hp

STANDARD TOOL SET
Four interchangeable working tools

STANDARD FUNCTIONS

01



ROTARY TILLAGE
Rotary tillage blades

02



WEEDING
Grass and weed removal

03



DITCHING
250-300 mm width

04



BACKFILLING
Backfill and level soil

ME-RT SERIES

SERIES TECHNICAL DATA SHEET

CONFIGURATION

MODEL / ENGINE

ME-RT SERIES I KOOP 195 SINGLE-CYLINDER DIESEL I 15 hp

STANDARD FUNCTIONS

ROTARY TILLAGE / WEEDING / DITCHING / BACKFILLING

TECHNICAL SPECIFICATIONS

PLATFORM TYPE **Remote-control crawler platform**	COOLING SYSTEM **Air cooling**
STARTING SYSTEM **Remote start / manual start**	REMOTE CONTROL DISTANCE **Up to 800 m**
WORKING WIDTH **800 mm**	TRAVEL SPEED **Up to 5 km/h**
MAXIMUM SLOPE **Up to 45 degrees***	TRACK WIDTH **150 mm**
ROTARY TILLING DEPTH **130-250 mm***	TRENCHING DEPTH **100-300 mm***
TRENCHING WIDTH **250-300 mm***	ATTACHMENT DRIVE **Belt drive**
CLUTCH **Automatic clutch**	DRIVE MOTORS **24V 800W x 2**
BATTERY **24V, 20Ah**	ROTOR SPEED / BLADES **360 r/min / 24 blades**
FUEL CONSUMPTION **Approx. 1.5 L/h**	FUEL TANK CAPACITY **5.5 L**
OVERALL DIMENSIONS **1800 x 750 x 700 mm**	OPERATING WEIGHT **390 kg, excluding tools**
PACKING DIMENSIONS **1900 x 1000 x 850 mm**	GROSS WEIGHT **500 kg, incl. four tool sets**

CONFIGURATION NOTE

Specifications marked * may vary with soil conditions, tool setup and operating method.
Final configuration is subject to the confirmed quotation and production specification.